

Product Name: Acetone



Grade: VLSI

Standard Package Information

Material Number :	650055, 650056, 650058, --
Container Type:	3 L, 5 L, 25 L Bottle, 200 L Drum

Contaminants	UM	Specifications
Assay	min. %	99,5
Insoluble Matter	v/v% max	0,05
Water	w% max	0.30
Acidity	to pass test	
Alkalinity	to pass test	
Trace Elements		
Aluminum (Al)	ppb max	50
Antimony (Sb)	ppb max	10
Arsenic (As)	ppb max	10
Barium (Ba)	ppb max	20
Bismuth (Bi)	ppb max	10
Boron (B)	ppb max	50
Beryllium (Be)	ppb max	10
Cadmium (Cd)	ppb max	10
Calcium (Ca)	ppb max	50
Chromium (Cr)	ppb max	10
Cobalt (Co)	ppb max	10
Copper (Cu)	ppb max	10
Gallium (Ga)	ppb max	10
Germanium (Ge)	ppb max	50
Gold (Au)	ppb max	10
Indium (In)	ppb max	10
Iron (Fe)	ppb max	50
Lead (Pb)	ppb max	10
Lithium (Li)	ppb max	20
Magnesium (Mg)	ppb max	50
Manganese (Mn)	ppb max	10
Molybdenum (Mo)	ppb max	10
Nickel (Ni)	ppb max	10
Platinum (Pt)	ppb max	20
Potassium (K)	ppb max	20
Silver (Ag)	ppb max	10
Silicon (Si)	ppb max	10
Sodium (Na)	ppb max	50
Strontium (Sr)	ppb max	10
Tin (Sn)	ppb max	10
Titan (Ti)	ppb max	10
Vanadium (V)	ppb max	10
Zinc (Zn)	ppb max	20